





Scale: 2/1



Lead wire diameter: $\phi 0.8$

Unit: mm




The I-t curves above are based on the average values of measurements obtained under testing conditions specified by our company. The information is for reference purposes only, and is not intended to infer any guarantees of performance.

Rated voltage	Certification	Range of rated current (I_N) ^{*1}	Rated breaking current	Current carrying capacity $1.0I_N$	Temp. rise $1.0I_N$	Overload operation
AC250V	UL Recognized	62mA - 10A	50A	Resistive circuit PF 0.95 - 1.0	15min or more after temperature stabilization occurs.	70K or less
	CSA Certified					

*1: Any rated current value can be selected within this range.




Scale: 2/1



Lead wire diameter: $\phi 0.8$

Unit: mm



The I-t curves above are based on the average values of measurements obtained under testing conditions specified by our company. The information is for reference purposes only, and is not intended to infer any guarantees of performance.

Rated voltage	Certification	Range of rated current (I_N) ^{*1}	Rated breaking current	Current carrying capacity $1.0I_N$	Temp. rise $1.0I_N$	Overload operation
AC250V	UL Recognized	100mA - 10A	50A	Resistive circuit PF 0.95 - 1.0	15min or more after temperature stabilization occurs.	70K or less
	CSA Certified					

*1: Any rated current value can be selected within this range.